

# Типы дугогасящих реакторов с сухой изоляцией



## ДГР с сухой изоляцией

тип	напряжение		
	6,6 кВ	11 кВ	
	диапазон регулировки тока [А - А]		
EDD	6/50/200	5 - 50	-
	10/30/200	-	3 - 30
EDD	6/65/250	6,5 - 65	-
	10/40/250	-	4 - 40
EDD	6/80/315	8 - 80	-
	10/50/315	-	5 - 50
EDD	6/105/400	10,5 - 105	-
	10/65/400	-	6,5 - 65
EDD	6/130/500	13 - 130	-
	10/80/500	-	8 - 80
EDD	6/165/630	16,5 - 165	-
	10/100/630	-	10 - 100
EDD	6/210/800	21 - 210	-
	10/130/800	-	13 - 130
EDD	6/260/1000	26 - 260	-
	10/160/1000	-	16 - 160
EDD	6/330/1250	33 - 330	-
	10/200/1250	-	20 - 200

# Типы дугогасящих агрегатов с сухой изоляцией



## ДГА с сухой изоляцией

тип		напряжение	
		6,6 кВ	11 кВ
		диапазон регулировки тока [A - A]	
ELD	6/50/200	5 - 50	-
	10/30/200	-	3 - 30
ELD	6/65/250	6,5 - 65	-
	10/40/250	-	4 - 40
ELD	6/80/315	8 - 80	-
	10/50/315	-	5 - 50
ELD	6/105/400	10,5 - 105	-
	10/65/400	-	6,5 - 65
ELD	6/130/500	13 - 130	-
	10/80/500	-	8 - 80
ELD	6/165/630	16,5 - 165	-
	10/100/630	-	10 - 100
ELD	6/210/800	21 - 210	-
	10/130/800	-	13 - 130
ELD	6/260/1000	26 - 260	-
	10/160/1000	-	16 - 160
	6/330/1250	33 - 330	-

# Типы дугогасящих агрегатов с масляной изоляцией



## ДГА с масляной изоляцией

тип		напряжение		
		6,6 кВ	11 кВ	38,5 кВ
		диапазон регулировки тока [А - А]		
ELD	6/50/200	5 - 50	-	-
	10/30/200	-	3 - 30	-
ELD	6/65/250	6,5 - 65	-	-
	10/40/250	-	4 - 40	-
ELD	6/80/315	8 - 80	-	-
	10/50/315	-	5 - 50	-
	35/15/315	-	-	1,5 - 15
ELD	6/105/400	10,5 - 105	-	-
	10/65/400	-	6,5 - 65	-
	35/18/400	-	-	1,8 - 18
ELD	6/130/500	13 - 130	-	-
	10/80/500	-	8 - 80	-
	35/22/500	-	-	2,2 - 22
ELD	6/165/630	16,5 - 165	-	-
	10/100/630	-	10 - 100	-
	35/28/630	-	-	2,8 - 28
ELD	6/210/800	21 - 210	-	-
	10/130/800	-	13 - 130	-
	35/35/800	-	-	3,5 - 35

# Типы дугогасящих агрегатов с масляной изоляцией



ДГА с масляной изоляцией				
	6/260/1000	26 - 260	-	-
ELD	10/160/1000	-	16 - 160	-
	35/45/1000	-	-	4,5 - 45
	6/330/1250	33 - 330	-	-
ELD	10/200/1250	-	20 - 200	-
	35/55/1250	-	-	5,5 - 55
ELD	10/250/1600	-	25 - 250	-
	35/70/1600	-	-	7 - 70
ELD	10/320/2000	-	32 - 320	-
	35/90/2000	-	-	9 - 90
ELD	10/400/2500	-	40 - 400	-
	35/110/2500	-	-	11 - 110
ELD	10/500/3150	-	50 - 500	-
	35/140/3150	-	-	14 - 140
ELD	10/630/4000	-	63 - 630	-
	35/180/4000	-	-	18 - 180

# Типы дугогасящих реакторов с масляной изоляцией



ДГР с масляной изоляцией				
тип		напряжение		
		6,6 кВ	11 кВ	38,5 кВ
		диапазон регулировки тока [А - А]		
END	6/50/200	5 - 50	-	-
	10/30/200	-	3 - 30	-
END	6/65/250	6,5 - 65	-	-
	10/40/250	-	4 - 40	-
END	6/80/315	8 - 80	-	-
	10/50/315	-	5 - 50	-
	35/15/315	-	-	1,5 - 15
END	6/105/400	10,5 - 105	-	-
	10/65/400	-	6,5 - 65	-
	35/18/400	-	-	1,8 - 18
END	6/130/500	13 - 130	-	-
	10/80/500	-	8 - 80	-
	35/22/500	-	-	2,2 - 22
END	6/165/630	16,5 - 165	-	-
	10/100/630	-	10 - 100	-
	35/28/630	-	-	2,8 - 28
END	6/210/800	21 - 210	-	-
	10/130/800	-	13 - 130	-
	35/35/800	-	-	3,5 - 35

# Типы дугогасящих реакторов с масляной изоляцией



## ДГР с масляной изоляцией

	6/260/1000	26 - 260	-	-
END	10/160/1000	-	16 - 160	-
	35/45/1000	-	-	4,5 - 45
	6/330/1250	33 - 330	-	-
END	10/200/1250	-	20 - 200	-
	35/55/1250	-	-	5,5 - 55
	10/250/1600	-	25 - 250	-
END	35/70/1600	-	-	7 - 70
	10/320/2000	-	32 - 320	-
END	35/90/2000	-	-	9 - 90
	10/400/2500	-	40 - 400	-
END	35/110/2500	-	-	11 - 110
	10/500/3150	-	50 - 500	-
END	35/140/3150	-	-	14 - 140
	10/630/4000	-	63 - 630	-
END	35/180/4000	-	-	18 - 180